

Package: Jmisc (via r-universe)

August 22, 2024

Type Package
Title Julian Miscellaneous Function
Version 0.3.1.1
Date 2011-12-26
Author TszKin Julian Chan <ctszkin@gmail.com>
Maintainer TszKin Julian Chan <ctszkin@gmail.com>
Description Some handy function in R.
License GPL (>= 2)
LazyLoad yes
Suggests testthat
Contact TszKin Julian Chan <ctszkin@gmail.com>
NeedsCompilation no
Date/Publication 2022-06-22 05:53:25 UTC
Repository <https://ctszkin.r-universe.dev>
RemoteUrl <https://github.com/cran/Jmisc>
RemoteRef HEAD
RemoteSha 0b141061bedc22bc9c7e7b6fa97dde67066f06a9

Contents

addCol	2
demean	3
evalFunctionOnList	3
generateSignificance	4
JBTest	5
label_both_parsed_recode	6
oapply	6
packages	7
recode	8
repCol	9

repRow	9
shift	10
sourceAll	11
splitBy	11
tic	12
%+%	13

Index	14
--------------	-----------

addCol	<i>Add a constant column to a data.frame or matrix</i>
--------	--

Description

Add a constant column to data.frame or matrix.

Usage

```
addCol(x, ..., value)
```

Arguments

x	data.frame or matrix
...	constants
value	vector a vector of constants

Value

a data.frame or matrix contains all columns in x and those constant columns.

Author(s)

TszKin Julian Chan <ctszkin@gmail.com>

Examples

```
d=data.frame(x=1:5,y=11:15)
addCol(d,a=1,b=2,c=3)
addCol(d,value=c(a=100,b=200,c=300))
```

demean	<i>Demean a vector or a matrix (by column)</i>
--------	--

Description

Demean a vector or a matrix (by column)

Usage

```
demean(x)
```

Arguments

x Vector or matrix

Value

Demeaned value of x

Author(s)

TszKin Julian Chan <ctszkin@gmail.com>

Examples

```
x<-matrix(1:20,ncol=2)
demean(x)
```

evalFunctionOnList	<i>Evaluate Function Under Local Variables</i>
--------------------	--

Description

This function evaluates a function `x` under an environment which is created by a list. All elements of the list is local to the function; other words all elements of the list can be accessed directly by the function. A new environment is created and each element of `variables` is assigned to the new environment. Then the environment associated with the `x` is updated with the new environment. Finally `x(...)` is evaluated and return the result.

Usage

```
evalFunctionOnList(x, variables = list(), ..., parent_env)
```

Arguments

x	A function to be called
variables	A list to be converted to an environment
...	Further arguments to x
parent_env	parent environment

Value

Return value of the `x(...)`.

Author(s)

TszKin Julian Chan <ctszkin@gmail.com>

See Also

[environment](#)

Examples

```
evalFunctionOnList(function() rnorm(n,mean,sd),list(n=5,mean=5,sd=1))
```

generateSignificance *Generate t-statistics, p-value and significance*

Description

Generate t-statistics, p-value and significance from estimates and its sd. Estimates and its SD is the first and second column respectively

Usage

```
generateSignificance(x, row_names)
```

Arguments

x	A matrix or data.frame
row_names	names of row

Value

a data.frame

Author(s)

TszKin Julian Chan <ctszkin@gmail.com>

Examples

```
n<-1000
x_data<-cbind(rnorm(n,mean=0),rnorm(n,mean=1))
x_estimates<-cbind(apply(x_data,2,mean),apply(x_data,2,sd)/sqrt(n))
generateSignificance(x_estimates)
generateSignificance(x_estimates,row_names=c("mean0","mean1") )
```

JBTest

p Value of Jarque Bera test

Description

Return the p Value of Jarque Bera test. The Jarque Bera test test the null hypothesis that the data are from a normal distribution.

Usage

```
JBTest(x)
```

Arguments

x data

Value

p Value of Jarque Bera test

Author(s)

TszKin Julian Chan <ctszkin@gmail.com>

Examples

```
JBTest(rnorm(50))
JBTest(rt(50,3))

n=100
# size
mean(replicate(n,JBTest(rnorm(100)))<0.05)

# power
mean(replicate(n,JBTest(rt(100,3)))<0.05)
```

label_both_parsed_recode

*Combine label_both and label_parsed in **ggplot2**.*

Description

Combine label_both and label_parsed in **ggplot2**. Also added a rename function to it see label_both and label_parsed in **ggplot2** for details.

Usage

```
label_both_parsed_recode(display_name)
```

Arguments

display_name A vector contains the display name. Names of the vector are the original name.

Value

A function similar to label_both and label_parsed in **ggplot2** for details.

Author(s)

TszKin Julian Chan <ctszkin@gmail.com>

References

<https://CRAN.R-project.org/package=ggplot2>

oapply

Outer apply

Description

Outer apply It use the expand.grid to compute all possible combination of X and Y, then call the mapply with the combination generated and FUN.

Usage

```
oapply(X, Y, FUN, switch_order = FALSE, ...)
```

Arguments

X	first argument to FUN
Y	second argument to FUN
FUN	a function to apply. See <code>mapply</code>
<code>switch_order</code>	Switch the order of X and Y in <code>expand.grid</code>
...	other arguments to <code>mapply</code>

Value

same as `mapply`.

Author(s)

TszKin Julian Chan <ctszkin@gmail.com>

See Also

[mapply](#)

Examples

```
oapply(11:15, 1:5, choose)
oapply(11:15, 1:5, choose, switch_order=TRUE)
```

packages

load packages with auto-installation

Description

load add-on packages. If the packages can not be found, `install.packages` is called.

Usage

```
packages(x, ...)
```

Arguments

x	name of the packages
...	arguments to <code>install.packages</code>

Author(s)

TszKin Julian Chan <ctszkin@gmail.com>

See Also

[require](#) [install.packages](#)

Examples

```
## Not run:  
packages("foreach")  
  
## End(Not run)
```

recode

Recode the value of a vector

Description

Recode the value of a vector or matrix.

Usage

```
recode(x, from, to)
```

Arguments

x	a vector or matrix
from	original value of x
to	new value of x

Value

recoded x

Author(s)

TszKin Julian Chan <ctszkin@gmail.com>

Examples

```
x=rep(1:5, each=2)  
recode(x, from=1:5, to=5:1)  
recode(x, from=1:5, to=11:15)
```

repCol	<i>Repeat a vector by col</i>
--------	-------------------------------

Description

Repeat a vector by col

Usage

```
repCol(x, n)
```

Arguments

x	vector or matrix
n	number of replication

Author(s)

TszKin Julian Chan <ctszkin@gmail.com>

See Also

[repRow](#)

Examples

```
repRow(c(a=1, b=2, c=3), 5)  
repCol(c(a=1, b=2, c=3), 5)
```

repRow	<i>Repeat a vector by row</i>
--------	-------------------------------

Description

Repeat a vector by row

Usage

```
repRow(x, n)
```

Arguments

x	vector or matrix
n	number of replication

Author(s)

TszKin Julian Chan <ctszkin@gmail.com>

See Also

[repCol](#)

Examples

```
repRow(c(a=1,b=2,c=3),5)
repCol(c(a=1,b=2,c=3),5)
```

shift	<i>shift a vector by shift_by unit</i>
-------	--

Description

Repeat a vector by row

Usage

```
shift(x, shift_by)
```

Arguments

x	a vector
shift_by	number of shift

Author(s)

TszKin Julian Chan <ctszkin@gmail.com>

Examples

```
d<-data.frame(x=1:15)
#generate lead variable
d$df_lead2<-shift(d$x,2)
#generate lag variable
d$df_lag2<-shift(d$x,-2)
```

sourceAll	<i>Source all the R files of a directory</i>
-----------	--

Description

Source all file with extension .r or .R

Usage

```
sourceAll(path = ".", ...)
```

Arguments

path	path of the directory
...	other arguments to source

Author(s)

TszKin Julian Chan <ctszkin@gmail.com>

See Also

[repCol](#)

Examples

```
## Not run:  
sourceAll()  
  
## End(Not run)
```

splitBy	<i>Split a vector by a sequence of length</i>
---------	---

Description

Split a vector by a sequence of length This function will split the vector x into length(x) subvector. The length of each subvector is given by by.

Usage

```
splitBy(x, by)
```

Arguments

x	A vector to be splitted
by	A vector of length

Value

a list of subvector

Author(s)

TszKin Julian Chan <ctszkin@gmail.com>

Examples

```
splitBy((1:10)*10,c(2,2))
splitBy((1:10)*10,c(2,3,4))
## Not run:
expect_equivalent(splitBy((1:10)*10,c(2,2)) , list(c(10,20),c(30,40)))
expect_equivalent(splitBy((1:10)*10,c(2,3,4)) , list( c(10,20) , c(30,40,50) ,c(60,70,80,90) ))

## End(Not run)
```

tic *Start Stop clock to measure performance*

Description

Start/clock to measure performance. Same as tic and toc in matlab

Usage

```
tic(name = ".time_Jmisc", envir = .GlobalEnv)

toc()
```

Arguments

name	Name of the temporary time variable
envir	environment of the temporary time variable

Author(s)

TszKin Julian Chan <ctszkin@gmail.com>

Examples

```
## Not run:
tic()
Sys.sleep(1)
toc

## End(Not run)
```

`%+%`*Concatenate two strings*

Description

Paste two strings together without separation.

Usage

```
s1 %+% s2
```

Arguments

s1	First String
s2	Second String

Value

```
paste(s1, s2, sep="")
```

Author(s)

TszKin Julian Chan <ctszkin@gmail.com>

Examples

```
cat("Hello" %+% "World")
```

Index

%+%, 13

addCol, 2

demean, 3

environment, 4

evalFunctionOnList, 3

generateSignificance, 4

install.packages, 7

JBTest, 5

label_both_parsed_recode, 6

mapply, 7

oapply, 6

packages, 7

recode, 8

repCol, 9, 10, 11

repRow, 9, 9

require, 7

shift, 10

sourceAll, 11

splitBy, 11

tic, 12

toc (tic), 12